


無熔線斷路器

無熔線斷路器 | BH系列

過負載/短路 保護兼用

框架容量(AF) 台芝型號			
外觀			
額定電流 In(A)(AT) 基準周圍溫度 40°C			
極數(P)			
額定 啟斷 容量 (KA)	IEC	60947-2	380V
	EN	60947-2	220V
	CNS	14816-2	110V
	Icu/Ics	AC	
外型 及 安裝 尺寸 (mm)			a
			b
			c
			ca
			bb
			aa

100 BH		
		
15,20,30,40,50, 60,75,100		
1	2	3
—		
5	5	
5	—	
25	50	75
95		
61		
77.5		
100		
-	25	50

100 BHU		
		
15,20,30,40,50, 60,75,100		
1	2	3
—		
5	10	10
10	—	
25	50	75
95		
61		
77.5		
100		
-	25	50

100 BHH		
		
15,20,30,40,50, 60,75,100		
1	2	3
—		
10	15	15
15	—	
25	50	75
95		
61		
77.5		
100		
-	25	50

100 BHS		
		
15,20,30,40,50, 60,75,100		
1	2	3
—	10	
10	22	
22	—	
25	50	75
95		
61		
77.5		
100		
-	25	50




**TAISHIBA
ELECTRIC**

Passion. Quality. Life

無
熔
線
斷
路
器

漏電斷路器 | NVL系列、NVS系列

漏電/過負載/短路 保護兼用

框架容量(AF)				50		50		50		
台芝型號				NVL-50		NVL-50U		NVL-50H		
外觀										
額定電流 In(A)(AT) 基準周圍溫度 40℃				15,20,30,40,50		15,20,30,40,50		15,20,30,40,50		
極數(P)				1P2線式	2P2E	1P2線式	2P2E	1P2線式	2P2E	
額定靈敏度 (mA)				30		30		30		
額定 啟斷 容量 (KA)	IEC	60947-2	440V	—		—		—		
	EN	60947-2	380V	—		—		—		
	CNS	5422	220V	5	5	5	10	10	15	
	Icu	AC	110V	5	—	10	—	15	—	
外型 及 安 裝 尺 寸 (mm)				a	25	50	25	50	25	50
				b	113		113		113	
				c	61		61		61	
				ca	77.5		77.5		77.5	
				bb	120		120		120	
				aa	-	25	-	25	-	25

50			50			50			30	50	
NVL-50S			NVL-50SU			NVL-50SH			NVS-30	NVS-50	
											
15,20,30,40,50			15,20,30,40,50			15,20,30,40,50			15,20,30	15,20,30,40,50	
1P2線式	2P2E	3P3E	1P2線式	2P2E	3P3E	1P2線式	2P2E	3P3E	2P	2P	3P
30-100-300-500可調式			30-100-300-500可調式			30-100-300-500可調式			30	30	
—			—			—			—	—	2.5
—			—			—			—	—	2.5
5	5		5	10		10	15		1.5	2.5	2.5
5	—		10	—		15	—		1.5	2.5	—
25	50	75	25	50	75	25	50	75	32	68.5	90.5
103			100			100			70	71	80.5
61			61			61			39	40	40
77			77			77			51	58.5	58.5
117			117			117			62	34	55
-	25	25	-	25	25	-	25	25	-	60	70